



GRIT	STANDARD VALUES FOR MICRO F-SERIES			US - SEDITOMETER			SEDIGRAPH 5000 D		
	Ds3% MAX	Ds50%	D 94% MIN	Ds3% MAX	Ds50%	D 94% MIN	Ds3% MAX	Ds50%	D 94% MIN
F 230	82	53.0 +/- 3.0	34	77.4	55.7 +/- 3.0	38.3	82.5	53.0 +/- 3.0	34.4
F 240	70	44.5 +/- 2.0	28	68.3	47.5 +/- 2.0	31.8	72.6	44.5 +/- 2.0	28.3
F 280	59	36.5 +/- 1.5	22	59.9	39.9 +/- 1.5	25.3	61.1	36.5 +/- 1.5	22.1
F 320	49	29.2 +/- 1.5	16.5	52.3	32.8 +/- 1.5	19.3	50.6	29.2 +/- 1.5	16.5
F 360	40	22.8 +/- 1.5	12	45.5	26.7 +/- 1.5	14.4	41.1	22.8 +/- 1.5	11.9
F 400	32	17.3 +/- 1.0	8	39.4	21.4 +/- 1.0	10	32.7	17.3 +/- 1.0	7.9
F 500	25	12.8 +/- 1.0	5	34.1	17.1 +/- 1.0	6.7	25.3	12.8 +/- 1.0	4.8
F 600	19	9.3 +/- 1.0	3	29.5	13.7 +/- 1.0	4.6	19	9.3 +/- 1.0	2.8
F 800	14	6.5 +/- 1.0	2	27.7	11.0 +/- 1.0	3.5	13.8	6.5 +/- 1.0	1.7
F 1000	10	4.5 +/- 0.8	1	22.7	9.1 +/- 0.8	2.4	9.6	4.5 +/- 0.8	0.7
F 1200	7	3.0 +/- 0.5	1 (at 80%)	20.4	7.6 +/- 0.5	2.4	6.4	3.0 +/- 0.5	0.7

Calculated on the basis of the Eppendorf-Photosedimentometer